




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁷ : B60J 5/04	A1	(11) International Publication Number: WO 00/63039 (43) International Publication Date: 26 October 2000 (26.10.00)
(21) International Application Number: PCT/CA00/00412 (22) International Filing Date: 19 April 2000 (19.04.00) (30) Priority Data: 60/130,138 20 April 1999 (20.04.99) US (71) Applicant (for all designated States except US): ATOMA INTERNATIONAL CORP. [CA/CA]; 521 Newpark Boulevard, Newmarket, Ontario L3Y 4X7 (CA). (72) Inventor; and (75) Inventor/Applicant (for US only): KIREJCZYK, Juliusz [CA/CA]; 141 Castle Rock Drive # 18, Richmond Hill, Ontario L4C 5N2 (CA). (74) Agent: IMAI, Jeffrey, T.; Magna International Inc., 337 Magna Drive, Aurora, Ontario L4G 7K1 (CA).	(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). Published <i>With international search report.</i> <i>Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>	

(54) Title: DOOR MODULE



(57) Abstract

A carrier plate (26) assembly is secured to an inner pannel (22) of a vehicle door. The carrier plate assembly includes a main section (46) having a forward edge and a rearward edge (50). A first flap section (54) is connected to the main section along the forward edge by a hinge and is detachably connected to the inner panel for movement about the hinge to provide access to the space without removing the entire carrier plate assembly. A second flap section (56) is connected to the rearward edge (50) by a second hinge to provide access to the hardware components in the space within the door.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakhstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

DOOR MODULE

Field of the Invention

The subject invention relates to a carrier plate assembly for a vehicle door having
5 inner and outer panels with an access opening in the inner panel. The carrier plate
assembly is removably secured to the inner panel to overlie and seal the opening and
provide selective access to the inner space of the door.

Background of the Invention

10 Inner and outer panels of a vehicle door are connected together to define a space
therebetween for housing various door hardware components. Access to the hardware
components for installation and repair is accommodated by the opening in the inner panel.
In most instances a carrier plate covers this opening. The carrier plate must be removed
from the inner panel for access to this inner space. Examples of such prior assemblies are
15 shown in U.S. Patent Nos. 5,050,350 to Bertolini et al. and 5,090,158 to Bertolini. The
removal of the carrier plate is time consuming and labor intensive.

The automotive parts supply industry has been evolving toward the supply of not
merely individual parts but the supply of modules. Modules have the advantage of
providing a greater number of parts and functionality into a single module while being
20 easier and quicker to install on an assembly line.

Door modules have been proposed which include a carrier plate having a number
of hardware components. In order to render the inner space more accessible without
totally disconnecting the carrier plate from the inner panel of the door, the entire carrier
plate has been hingedly connected to the door panels, as is shown in U.S. Patent Nos.
25 4,866,883 to Brown et al. and 5,906,072 to Feige et al. The prior art hinged carrier plates
are relatively large and are actually the majority of the inner panel of the door itself. The
structural integrity of the door is therefore compromised. In addition, the known hinged
carrier plates are labor intensive to disconnect.

In addition to the access problem with the prior art assemblies, the carrier plates
30 must be sealed to the inner door panel to prevent moisture from gaining access to the inner
space and the hardware disposed therein. Many of the prior art door modules have a
disadvantage in that once the module is installed, a separate vapor barrier must be utilized

in order to seal the door and maintain a relatively dry environment for the operation of the hardware components of the door.

Accordingly, there is a need for a carrier plate which can be efficiently manipulated to provide access to the interior space of the door while adequately sealing
5 the door to prevent the ingress of moisture.

Summary of the Invention

The subject invention is an improvement over the prior art carrier plates that are mounted to an inner panel of a vehicle door. The carrier plate assembly includes a main
10 section having at least one mounting area where door hardware is mountable thereon. At least one flap section is connected to the main section by a hinge and is movable about the hinge to provide access behind the inner panel of the door without removing the carrier plate.

Accordingly, the subject invention provides a carrier plate which may be pre-
15 assembled with hardware. The carrier plate has a flap section extending from the main section. The main section may be mounted to the inner door panel while allowing access to the interior by opening the flap section. Once the installation of the carrier plate is complete, the flap section is folded against the inner panel and sealed thereto to hermetically seal the door. In the event the hardware in the inner space of the door must
20 be serviced at a later date, the flap section may be opened without removing the entire carrier plate to gain access to the hardware needing repair.

Brief Description of the Drawings

Other advantages of the present invention will be readily appreciated as the same
25 becomes better understood by reference to the following detailed description when considered in connection with the accompanying drawings wherein:

Figure 1 is a side elevational view of a vehicle door with a carrier plate assembly of the subject invention shown in phantom;

Figure 2 is a side elevational view of the carrier plate of Figure 1;

30 Figure 3 is a cross sectional view taken along line 3-3 of Figure 1;

Figure 4 is a cross sectional view taken along line 4-4 of Figure 1;

Figure 5 is a cross sectional view taken along line 5-5 of Figure 1;

Figure 6 is a cross sectional view taken along line 6-6 of Figure 1;

Figure 7 is a partial sectional view of a regulator cable attachment of Figure 6;

Figure 8 is a cross sectional view taken along line 8-8 of Figure 1;

Figure 9 is a partial sectional view of a door module attachment of Figure 8;

5 Figure 10 is a side elevational view of a vehicle door incorporating an alternative embodiment of the carrier plate assembly of the present invention;

Figure 11 is an exploded perspective view of the alternative carrier plate assembly of Figure 10;

Figure 12 is a perspective view of the alternative carrier plate assembly of Figure
10 10;

Figure 13 is a fragmentary perspective view of the vehicle door in combination with the alternative carrier plate assembly of Figure 10 and with the an open position shown in phantom;

Figure 14 is a cross sectional view taken along line 14-14 of Figure 10; and

15 Figure 15 is a cross sectional view taken along line 15-15 of Figure 10.

Detailed Description of the Preferred Embodiments

Referring to the Figures, wherein like numerals indicate like or corresponding parts throughout the several views, a vehicle door for hinged mounting on a vehicle body is
20 generally shown at 20 in Figure 1.

The door 20 includes an inner panel 22 and an outer panel 24 connected together about peripheries thereof to define an inner space or cavity therebetween for housing door hardware components. The panels 22, 24 are typically made of sheet metal and are hemmed together about respective peripheries. The inner panel 22 preferably has a pair of
25 openings 69, 71 formed therein for access to the space between the panels 22, 24. A bridge 70 extends vertically between the openings 69, 71 to present a structure for supporting an armrest. The bridge 70 is preferably integral with the inner panel 22. Additionally, the bridge 70 enhances stiffness of the door 20.

Referring also to Figure 2, a carrier plate assembly, generally indicated at 26, is
30 secured to the inner panel 22 and is sized to cover both of the openings 69, 71. The carrier plate assembly 26 includes a main section 46 which is secured to the inner panel 22 by clips, fasteners, or the like. Preferably, the main section 46 is secured to the inner panel

22 at the bridge 70. The main section 46 has at least one mounting area where door hardware is mountable thereon as is discussed in greater detail below. The main section 46 includes a forward edge 48 and a rearward edge 50. A first flap section 54 extends from the main section 46 at a hinge and is detachably connected to the inner panel 22 for pivotal movement about the hinge. Similarly, a second flap section 56 is connected to the rearward edge 50 by a second hinge. Preferably, the main section 46 and flap sections 54, 56 are integrally formed of an organic polymeric material, i.e. plastic, whereby the hinges are integral living hinges.

The first flap section 54 has a mounting area in the form of hole 68 for mounting a conventional audio speaker 28. Other mounting areas are disposed on the main section 46 of the carrier plate assembly 26 for mounting various door components thereon. It is preferred that substantially all of the hardware components for the door are mounted to the carrier plate assembly 26. The carrier plate assembly 26 of this embodiment is preferably designed of a non-structural material such that the hardware components are transported thereon. The hardware components can be then mounted directly to the inner panel 22 of the door 20 as is discussed below. The carrier plate assembly 26 positions or aligns each of the components at the desired position on the inner panel 22. The non-structural material of the carrier plate assembly 26 is sufficiently supportive to transport the carrier plate assembly 26 with the hardware components thereon.

As illustrated, a pair of rails 72 are mounted to the main section 46. Once the carrier plate assembly 26 is installed, the rails 72 are bolted or otherwise affixed to the inner panel 22 for guiding a window 34 therealong. A window regulator component 29, either manual or power, is also mounted to the main section 46. The window regulator component 29 is also mounted to the inner panel 22 once the carrier plate assembly 26 is mounted to the door 20. The window regulator component 29 includes a series of cables 74 connected between a motor 30 and the window 34 for moving the window 34 along the rails 72. The cables 74 pass between the bridge 70 and the carrier plate assembly 26.

As illustrated, the motor 30 can be mounted forwardly of the rails 72 rather than between the rails 72 as is conventional. The forward mounting of the motor 30 is advantageous in that the mass of the motor 30 is closer to the axis of rotation of the door 20 during opening and closing thereby reducing the inertia of the door 20.

Door latch components, including a latch, an inside release handle and an inside

door lock mechanism are mounted on the carrier plate assembly 26.

A bead of sealing compound (not shown) may be disposed about the periphery of the main section 46 and the flap sections 54, 56 for sealing the carrier plate assembly 26 to the inner panel 22, thereby defining a "dry" side on the inner space and a "wet" side on the exterior. The sealing surface of the inner panel 22 follows the shape of the entire carrier plate assembly 26. Any control cables or the like which must pass through the carrier plate assembly panel 26 can be sealed with grommets as is conventional in the art.

Referring to the sectional views of Figures 3 through 9, the carrier plate assembly 26 is illustrated in greater detail. In particular, Figure 3 further illustrates the first flap section 54 and Figures 4, 5, 6 and 8 further illustrate the main section 46 of the carrier plate assembly 26. As shown in Figure 4, the window regulator component 29 is mounted to the main section 46 by a bracket 31. As shown in Figures 5-7, the main section 46 of the carrier plate assembly 26 also includes integrally molded cable guides 76 for housing the cables 74 that move the window 34. As appreciated, there may also be integrally molded guides for an electrical harness.

The carrier plate assembly 26 is pre-assembled and shipped to the assembly plant in the pre-assembled condition. On the assembly line, the carrier plate assembly 26 is placed on the inner panel 22 with the rails 72 being positioned in the inner space. The carrier plate assembly 26 seals to the continuous sealing surface of the inner panel 22. Fasteners (not shown) attach the main section 46 of the carrier plate assembly 26 to the inner panel 22 in the region of the bridge 70. The door latch 44, which was attached to the carrier plate assembly 26 for shipping, is secured to the end region of door panel 22.

The flap sections 54, 56 are hinged open to provide access to the inner space. Hence, an installer may install the door latch 44 and make all necessary connections with inner and outer door handles through the second or rear flap section 56. Electrical connections to the speaker 28 and the wiring harness 32 can be made through the first or forward flap section 54. The window 34 can be connected to the control cables 74 through both flap sections 54, 56. Once all of the mountings and connections have been made, the flap sections 54, 56 are pivoted about their respective hinges to the closed position overlying and sealing the openings 69, 71, as by a gasket seal or adhesive 60.

An interior door panel 78, best shown in Figures 3-6 and 8, can then be installed to the inner panel 22 to present an aesthetically pleasing covering.

Referring now to Figure 10, an alternative embodiment of the subject invention is illustrated wherein like numerals increased by 100 indicate like or corresponding parts throughout the several views. A door 120 is illustrated having a similar construction as the door 20 of the primary embodiment. In particular, the door 120 includes an inner
5 panel 122 and an outer panel 124 connected together in spaced relationship with one another to define an inner space therebetween for housing door hardware components. The inner panel 122, however, has only one large opening 169 for providing access into the space as is shown in Figure 13.

A carrier plate assembly 126 is formed of a rigid material is illustrated in this
10 embodiment. The rigid carrier plate assembly 126 is designed to support a number of the door hardware components thereon during the shipping of the plate assembly 126. In particular, an audio speaker 128, motor 130, and electrical harness 132 are all illustrated as being supported by the carrier plate assembly 126. The motor 130 and electrical harness 132 are preferably part of a window regulator component 129 for moving a window 134.
15 As appreciated, any hardware or like component which is part of the door 120 may be mounted to the carrier plate assembly 126.

The rigid carrier plate assembly 126 of this alternative embodiment is designed of a structural material such that the hardware components transported thereon remain mounted to the carrier plate assembly 126. Hence, the carrier plate assembly 126 is first
20 installed onto the door 120, the hardware components are then connected, and no additional mounting of the parts is necessary.

Referring to Figures 11 and 12, the carrier plate assembly 126 is shown in greater detail with the speaker 128, motor 130 and electrical harness 132 spaced therefrom. The carrier plate assembly 126 includes an outer face, as shown in Figure 11, and an inner
25 face, as shown in Figure 12. The speaker 128, motor 130 and electrical harness 132 are preferably mounted to the outer face of the carrier plate assembly 126. Integral pockets and/or mounts 136, 138, 140 are included on the carrier plate assembly 126 for supporting the various hardware components. In particular, the motor 130 is supported by the mount 136. A gearbox (not shown) is disposed within the pocket formed by mount 136 (best
30 shown in Figure 12). The mount 136 also includes a sealed opening for allowing the motor 130 to engage the gearbox. The mount 136 can be designed to directly accommodate the gears of the gearbox thereby allowing a separate gearbox housing to be

eliminated. The mount 140 is molded at the desired location to support a door handle mechanism 142. The platform mount 138 is presented to reinforce an armrest (not shown). The electrical harness 132 electrically interconnects the motor 130 and control buttons (not shown). A door latch 144 is connected via a cable to the door handle 142.

5 As is common with the carrier plate assembly 26 of the first embodiment, the carrier plate assembly 126 includes a main section 146 secured to the inner panel 122 by clips, fasteners, or the like. The main section 146 includes a forward edge 148 and a rearward edge 150 with an arm 152 extending forwardly from the forward edge 148. A first flap section 154 is connected to the main section 146 by a hinge and is detachably
10 connected to the inner panel 122 for movement about the hinge to access the inner space without removing the entire carrier plate assembly 126. Preferably, the first flap section 154 is disposed above the arm 152 and along the forward edge 148. A second flap section 156 is connected to the rearward edge 150 by a second hinge.

The main section 146 and the flap sections 154, 156 of the carrier plate assembly
15 126 are preferably formed of a rigid material. Even more preferably, the main section 146 and flap sections 154, 156 are formed of an integral organic polymeric material, i.e. plastic. The flap sections 154, 156 are connected to the rigid main section 146 by rivets 158, or the like, as shown in Figure 12. As appreciated, the flap sections 154, 156 may be alternatively adhered to the main section 46 by an adhesive. The flap sections 154, 156
20 are preferably formed of a soft or malleable material such that a living hinge can be formed on the flap sections 154, 156. In the event the flap sections 154, 156 are of paper board or the like, a moisture impervious layer or sheet (not shown) is adhered thereto to present a moisture barrier.

Tape 160 (shown in Figure 10) or other like adhesive may be employed to secure
25 the flap sections 154, 156 to the inner panel 122. A bead of sealing compound (not shown) may be disposed about the periphery of the main section 146 and the flap sections 154, 156 for sealing the carrier plate assembly 126 to the inner panel 122, thereby defining a "dry" side on the interior of the space and a "wet" side on the exterior. In particular, the carrier plate assembly 126 is sealed to an inner side of the inner panel 122 (best shown in
30 Figure 14).

The rigid main section 146 includes reinforcing ribs 162 on both sides thereof. The main section 146 is generally rectangular and includes two vertically curved channels

164, which support integrally molded cable guides 177 and pulleys 175. The channels 164 define the two curved edges 148, 150 which curvature reflects that of the window 134.

Hence, the edges 148, 150 form the rails for window regulator lift plates 166. The integrally molded cable guides 177 and pulleys 175 receive window regulator cables (not shown) for moving the window 134. In particular, the window regulator cables are routed through the guides 177 and pulleys 175 and then attached to the lift plates 166. The arm 152 also has a mount in the form of an oval hole 168 in the main section 146 with the audio speaker 128 disposed in the hole 168.

Figures 14 and 15 illustrate cross-sectional views through the inner 122 and outer 124 panels and the alternative carrier plate assembly 126 of Figure 10.

The carrier plate assembly 126 of this alternative embodiment is pre-assembled and shipped to the assembly plant in a similar pre-assembled condition as the first embodiment. On the assembly line, the carrier plate assembly 126 is placed on the inner panel 122. As discussed above, the carrier plate assembly 126 is sealed to an inner side of the inner panel 122 (best shown in Figure 14). Fasteners (not shown) attach the main section 146 of the carrier plate assembly 126 to the inner panel 122.

The flap sections 154, 156 are hinged open to provide access to the interior space. Hence, an installer may install the door latch 144 and make all necessary mechanical and electrical connections with inner and outer door handles through the second or rear flap section 156. Electrical connections to the speaker 128 and the wiring harness 132 can be made through the first or forward flap section 154. The window 134 can be connected to the lift plates 166 through both flap sections 154, 156. As discussed above, no additional mounting of the hardware components is necessary. Once all of the connections have been made, the flap sections 154, 156 are pivoted about their respective hinges to the closed position overlying and sealing the opening 169.

The flaps sections 154, 156 are sealed to the inner panel 122 to seal the periphery of the carrier plate assembly 126. An interior door panel, not shown but similar to the door panel of the primary embodiment, can then be installed to the inner panel 122 to present an aesthetically pleasing covering.

Many modifications and variations of the present invention are possible in light of the above teachings. The invention may be practiced otherwise than as specifically described within the scope of the appended claims.

What is claimed is:

1. A carrier plate assembly adapted to be secured to an inner panel of a vehicle door,
said assembly comprising;
a main section having at least one mounting area where door hardware is
5 mountable thereon, and
at least one flap section extending from said main section and pivotal for providing
access behind the inner panel of the door.
2. An assembly as set forth in claim 1 wherein said main section and said flap section
are integrally connected together by a living hinge.
- 10 3. An assembly as set forth in claim 1 wherein said main section is formed of a rigid
material.
4. An assembly as set forth in claim 3 wherein said flap section consists of a different
material than said main section.
5. An assembly as set forth in claim 3 wherein said flap section is formed of a
15 moisture impervious material.
6. An assembly as set forth in claim 3 wherein said main section includes integral
channels defining a pair of guides for regulating movement of a window.
7. An assembly as set forth in claim 6 wherein said channels include lift plates in
sliding engagement within said channels for supporting the window.
- 20 8. An assembly as set forth in claim 3 wherein said main section further includes
reinforcing ribs.
9. An assembly as set forth in claim 3 wherein said main section includes integral
pockets for supporting various hardware components.
10. An assembly as set forth in claim 1 further including adhesive tape for securing
25 said flap section to the inner panel.
11. An assembly as set forth in claim 1 wherein said mounting area comprises a hole
for receiving an audio speaker.
12. An assembly as set forth in claim 3 wherein said main section includes a forward
edge and a rearward edge and an arm extending forwardly from said forward edge, said
30 flap section being disposed above said arm and along said forward edge.
13. An assembly as set forth in claim 12 wherein said mounting area comprises a hole
disposed in said arm for receiving an audio speaker.

14. An assembly as set forth in claim 12 including a second flap section connected to said rearward edge by a second hinge.
15. An assembly as set forth in claim 2 wherein said main section includes a forward edge and a rearward edge, said hinge for said flap section being disposed along said
- 5 forward edge, and including a second flap section integrally connected to said rearward edge by a second living hinge.
16. An assembly as set forth in claim 15 wherein said main section has an integrally molded cable guide adapted to receive a cable of a window regulator.
17. An assembly as set forth in claim 16 wherein said main section has a window
- 10 regulator assembly mounted thereto.




FIG-1




FIG-2

FIG-5




FIG-4





FIG-3



4/8




FIG-9









FIG-8

6/8

FIG-10**FIG-11**

7/8

FIG-12**FIG-13**

8/8




FIG-14




FIG-15

INTERNATIONAL SEARCH REPORT

International Application No

PCT/CA 00/00412

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 B60J5/04

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 B60J

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

WPI Data, PAJ

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 5 050 350 A (CARLO BERTOLINI) 24 September 1991 (1991-09-24) cited in the application column 4; figures	1
A	US 5 090 158 A (CARLO BERTOLINI) 25 February 1992 (1992-02-25) cited in the application column 6, line 5 - line 28; figures	1
A	US 4 866 883 A (DAVID BROWN) 19 September 1989 (1989-09-19) cited in the application abstract; figures	1

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

9 August 2000

Date of mailing of the international search report

16/08/2000

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Vanneste, M

INTERNATIONAL SEARCH REPORT

Int'l. Application No

PCT/CA 00/00412

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A,P	US 5 906 072 A (STEFAN FEIGE) 25 May 1999 (1999-05-25) cited in the application abstract; figures	1
A	DE 197 07 850 C (BROSE FAHRZEUGTEILE) 12 March 1998 (1998-03-12) abstract; figures	1
A	DE 196 53 501 A (YAZAKI CORP.) 14 March 2000 (2000-03-14) claim 1; figures	1

INTERNATIONAL SEARCH REPORT

Information on patent family members

Int: lonal Application No

PCT/CA 00/00412

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5050350 A	24-09-1991	FR 2648762 A BR 9003010 A CA 2017942 A DE 69000375 D DE 69000375 T EP 0406034 A JP 3121924 A	28-12-1990 20-08-1991 27-12-1990 12-11-1992 01-04-1993 02-01-1991 23-05-1991
US 5090158 A	25-02-1992	FR 2643860 A BR 9000976 A CA 2010745 A DE 69001370 D DE 69001370 T EP 0385823 A JP 2270632 A	07-09-1990 19-02-1991 03-09-1990 27-05-1993 18-11-1993 05-09-1990 05-11-1990
US 4866883 A	19-09-1989	EP 0336565 A JP 2011414 A	11-10-1989 16-01-1990
US 5906072 A	25-05-1999	DE 19732225 A FR 2766428 A IT MI981278 A JP 11048781 A	11-02-1999 29-01-1999 06-12-1999 23-02-1999
DE 19707850 C	12-03-1998	BR 9807798 A CN 1248205 T WO 9838057 A EP 0961703 A	22-02-2000 22-03-2000 03-09-1998 08-12-1999
DE 19653501 A	03-07-1997	JP 9169214 A US 6035601 A	30-06-1997 14-03-2000